



Appliance Tester/Power Analyzer

Compact, battery operated device for analyzing AC power loads

With PC interface plus datalogging

Features:

- Four simultaneous displays of Watts. Power Factor or VA, Voltage or Hz, Amps
- True RMS Voltage & Current measurements of sine, square, triangular and distorted wave forms with a crest factor < 5
- Max, Data Hold and Overload Protection
- Battery or AC adaptor provides line isolation
- Plug device to be tested directly into the Power Analyzer
- Sampling (update) rate is 2.5 times/second
- Windows® 95/98/NT/2000/XP/ME software allows user to download stored data or save data directly, and to create an ASCII file. Computations include phase angle, apparent and reactive power, consumption and cost, and power factor correction
- · Complete with Windows compatible software, cable, 8 x AA batteries, power cord, 117 VAC adaptor and case

Applications:

- Measure and Audit power consumption of single phase devices
- Evaluate load performance under varying line conditions
- · Demonstrate effectiveness of power conservation efforts
- Characterize device AC power requirements

(Single record storage or continuous datalogging)

Model 380801

Used for data acquisition when connected to a PC

Model 380803 Datalogger

Built-in Datalogger stores up to 1,012 readings

Ordering Information:

380801	.True RMS Single Phase Power Analyzer
380801-NIST	.380801 with NIST Certificate
380803	.True RMS Power Analyzer Datalogger
380803-NIST	.380803 with NIST Certificate
PR20	.Portable Thermal Printer
757057	.Thermal Paper for PR20 (6 pack)
USB100	.RS-232 to USB Adaptor





Optional Thermal Printer (PR20) prints text or graphics with fixed intervals or continuous



Software included to download and store data to a PC



Built-into heavy duty carrying case.

Specifications:	Range	Resolution	Basic Accuracy (%rdg)	Input Signal Range
Watt	200/2000W	0.1/1W	$\pm (0.9\% + 4d)@50/60Hz$	300V, 20A, 40-400Hz
Power Factor	0.5 to 1.0	0.001	(Based on W, V, A)	250V, 20A, 50/60Hz
Voltage	200.0/750V	0.1/1V	±(0.5%)	750VAC
Current	2/20A via terminals		±(0.5%)	(Fuse Protection)
	2/15A via sockets			
Frequency	40Hz to 20kHz	1Hz to 10Hz	±(0.5%)	
Dimensions/Weight	13.9 x 11.8 x 3.9" (35	2 x 300 x 100mm	n) / 3.6 lbs. (1.6 kg)	







